

Struttura in metallo verniciato e pendagli in cristallo.
Illuminazione a LED.


Painted metal frame and crystal pendants. LED lighting.

Gestell aus lackiertem Metall und Kristallanhänger.
LED-Beleuchtung.

Structure en métal peint et pendentifs en cristal.
LED éclairage.

СТРУКТУРА ИЗ ОКРАШЕННОГО МЕТАЛЛА И ХРУСТАЛЬНЫЕ ПОДВЕСЫ.

Standard finishings



V95 Bianco opaco
Matt white



F01 Foglia oro
Gold leaf

Transparent pendants



TR Trasparente
Transparent

Family

Ceiling




Suspension




Applique




Standard cables for all suspensions



BLINK S1




Suspension  

TECHNICAL INFORMATION

Ø 24 cm / 9.44"
H 18 cm / 7.08"

DOWN: LED x 4 W CRI>90
 3000 K - 590 Nominal lm
Dimmable: 0 - 10 V

BLINK S6




Suspension  

TECHNICAL INFORMATION

DOWN: LED x 24 W CRI>90
 3000 K - 3540 Nominal lm
Dimmable: 0 - 10 V

BLINK S42




Suspension  

TECHNICAL INFORMATION

Ø 42 cm / 16.53"
H 26 cm / 10.23"

DOWN: LED x 21 W CRI>90
 3000 K - 2980 Nominal lm
Dimmable: 0 - 10 V

BLINK S60




Suspension  

TECHNICAL INFORMATION

Ø 60 cm / 23.62"
H 30 cm / 11.81"

DOWN: LED x 41 W CRI>90
 3000 K - 5960 Nominal lm
Dimmable: 0 - 10 V

BLINK C3 LN 125




TECHNICAL INFORMATION

L 125 cm / 49.21"
SP 20 cm / 7.87"
H max 170 cm / 66.92"

DOWN: LED x 12 W CRI>90
 3000 K - 1770 Nominal lm
Dimmable: 0 - 10 V

BLINK C6 LN 175




TECHNICAL INFORMATION

L 175 cm / 68.89"
SP 20 cm / 7.87"
H max 170 cm / 66.92"

DOWN: LED x 24 W CRI>90
 3000 K - 3540 Nominal lm
Dimmable: 0 - 10 V

BLINK C3 RD 60




TECHNICAL INFORMATION

Ø 60 cm / 23.62"
H max 170 cm / 66.92"

DOWN: LED x 12 W CRI>90
 3000 K - 1770 Nominal lm
Dimmable: 0 - 10 V

BLINK C6 RD 80



TECHNICAL INFORMATION

Ø 80 cm / 31.49"
H max 170 cm / 66.92"

DOWN: LED x 24 W CRI>90
 3000 K - 3540 Nominal lm
Dimmable: 0 - 10 V

BLINK LED PL90


Ceiling



TECHNICAL INFORMATION

Ø 90 cm / 35.43"
H 15 cm / 5.90"

DOWN: LED x 47 W CRI>90
 3000 K - 6700 Nominal lm
Dimmable: 0 - 10 V



BLINK LED PL60


Ceiling



TECHNICAL INFORMATION

Ø 60 cm / 23.62"
H 14 cm / 5.51"

DOWN: LED x 41 W CRI>90
 3000 K - 5960 Nominal lm
Dimmable: 0 - 10 V



BLINK LED PL42


Ceiling





TECHNICAL INFORMATION

Ø 42 cm / 16.53"
H 12 cm / 4.72"

DOWN: LED x 21 W CRI>90
 3000 K - 2980 Nominal lm
Dimmable: 0 - 10 V



BLINK LED A1 G**Applique****TECHNICAL INFORMATION****L** 24 cm / 9.44"**SP** 28.5 cm / 11.22"**H** 14 cm / 5.51"**UP:** LED x 4 W CRI>90 3000 K
590 Nominal lm**DOWN:** LED x 4 W CRI>90 3000 K
590 Nominal lm**Dimmable:** 0 - 10 V**BLINK LED A1 P****Applique****TECHNICAL INFORMATION****L** 18 cm / 7.09"**SP** 23 cm / 9.06"**H** 14 cm / 5.51"**UP:** LED x 3 W CRI>90 3000 K
425 Nominal lm**DOWN:** LED x 3 W CRI>90 3000 K
425 Nominal lm**Dimmable:** 0 - 10 V